irradiating at least said gap with an electron beam from electron emitting means disposed apart from said first and second electrically conductive members, within an atmosphere containing a carbon compound; and

applying a voltage to said first and second electrically conductive members.

14

المين

(New) A manufacturing method of an electron-emitting device, comprising the steps of:

disposing an electrically conductive member having a gap, on a substrate;

irradiating at least said gap with an electron beam from electron emitting means disposed apart from said electrically conductive member, within an atmosphere containing a carbon compound; and

applying a voltage to said electrically conductive member.

(New) A manufacturing method of an electron-emitting device, comprising the steps of:

disposing a first electrically conductive member and a second electrically conductive member so as to form a gap therebetween, on a substrate;

irradiating at least said gap with an electron beam from electron emitting means disposed apart from said first and second electrically conductive members, within an atmosphere containing a carbon compound; and

applying a voltage to said first and second electrically conductive members, within the atmosphere containing the carbon compound.

(New) A manufacturing method of an electron-emitting device, comprising the steps of:

disposing an electrically conductive member having a gap, on a substrate;

irradiating at least said gap with an electron beam from electron emitting means disposed apart from said electrically conductive member, within an atmosphere containing a carbon compound; and

applying a voltage to said electrically conductive member, within the atmosphere containing the carbon compound.—

REMARKS

Claims 1-11 and 15-18 are now pending in this application.1

Claims 15-18 have been added to provide Applicants with a more complete scope of protection.

Claims 1-11 were allowed in the Notice of Allowance dated December 4, 2001.